

SmartGuard™ Modular & Evidence Lockers



SmartGuard™
SECURE ASSET CONTROL

powered by **LEID**
Products



SPECIFICATIONS

Access

- Electronic rotary latch locks on doors
- Keypad-LCD using passcode with optional card reader
- Biometric access with computer kiosk

Cabinets

- All steel construction
- 16-gauge sides, shelves, and frame
- Welded frame with riveted assembly

Doors

- 16-gauge steel
- Electronic rotary latch locks on doors
- Spring-loaded front doors automatically open when unit is accessed
- Manual override on doors
- Optional rear door for pass-through installation - key cam lock

Finish

- Gray powder coat

Installation/Electronics

- Each separate location requires a controller, maximum operating capacity is 8 units
- 120/240 VAC 50/60 Hz 15-amp circuit (lead unit with controller)
- Units can be installed individually or side-byside
- Unit requires secure attachment to wall or floor and units in multiple installation must be secured to each other
- Optional 24" high pedestal



DIMENSIONS		
Cabinet or Locker	Overall Unit Dims	Approx. Compartment Door Size
2W2D-4L	33.5"Wx39.75"Hx16"D	16"Wx15.125"Hx14.5"D
2W5D-10S	15.5"Wx39.75"Hx16"D	6.5"Wx5.75"Hx14.5"D
4W5D-20S	27.75"Wx39.75"Hx16"D	6.5"Wx5.75"Hx14.5"D
2W5D-10ML	43.5"Wx39.75"Hx16"D	20"Wx6.5"Hx14.5"D
2W5D-10M2	36.5"Wx39.75"Hx16"D	16.5"Wx6.5"Hx14.5"D

- Series 181 offers choice of 1-6, 9 or 12 doors
Overall unit measurement 18"Wx17.5"Dx63.1875"H
Inside unit depth 16" front load, 15" rear load
- Weight: 20-door locker 200 lbs.



More electronic locker configurations and their dimensions can be found at SecureAssetControl.com